

## Silicone Thermal Grease TGP-600 6W/Mk



### Applications

- CPU, GPU (Notebooks, Desktops, Servers)
- Custom ASICS Chips
- LED Applications
- Digital Mobile Convergence
- Telecommunication Equipment

TGP thermal compound is a silicone-based thermal grease made from a silicone fluid with thermally conductive material and metal oxide fillers. The product offers high thermal conductivity, virtually no wide operating bleed or evaporation over temperature range.

TGP series has low viscosity and easy handling properties to comparable grease. So it easily coats the surface of the component. Especially it has superior wetting properties and so completely fills the microscopic surface of the component, resulting in very low thermal resistance.

TGP series is an efficient thermal coupler, effective and positive heat sink sealers and heat transfer agent. TGP series is very stable at elevated temperature. It does not dry out, settle or harden. So it is superior reliable properties at temperature range.

**Available in container tubs for mass production.**

Item	Unit	Specification	Test Method
Appearance	-	Grey	Visual
Specific Gravity	-	2.6	ASTM D70
Viscosity	Pa • s	230	Brookfield
Thermal Conductivity	W/Mk	6.0	Laser Flash
Thermal Resistance	°C-cm <sup>2</sup> /W	0.13 @ 10 psi	ASTM D5470
Insulation Strength	-	-	-
Operating Temperature	°C	0-120	-
RoHS	-	-	N/D
Storage Temperature	-	Room Temperature	-

### AMEC Thermasol

1-2 Steam Mill Lane, Great Yarmouth, Norfolk, NR31 0HP

Telephone: +44(0) 1493 668622 Fax: +44(0) 1493 668623

Email: [sales@amecthermasol.co.uk](mailto:sales@amecthermasol.co.uk) Website: [www.amecthermasol.co.uk](http://www.amecthermasol.co.uk)